



Model: HC100

BCI Group: 27



HIGH RATE DISCHARGE @ 77° (25°C) - STARTING			
5 Seconds	10 Seconds	20 Seconds	30 Seconds
1950 Amps	1745 Amps	1500 Amps	1355 Amps

EXTENDED DISCHARGE @ 77° (25°C) to 10.02V - DEEP CYCLE						
5 Min	15 Min	1 Hour	3 Hour	5 Hour	10 Hour	20 Hour
382 Amps	188 Amps	60 Amps	25.1 Amps	17.2 Amps	9.65 Amps	5.15 Amps

PERFORMANCE FEATURES

- PHCA: 1950A at 80°F (27°C) for 5 seconds
- CCA: 950A at 0°F (-18°C)
- CA/MCA: 1170A at 32°F (0°C)
- HCA: 1380A at 80°F (27°C)
- 100AH @20 Hr Rate
- Reserve capacity: 185 minutes
- Short circuit current: 3500A
- Operation temperature range: -5°F (-15°C) to 122°F (50°C)

BATTERY DESIGN

- 12V VRLA **Starting/Deep Cycle** Battery
- Absorbed Glass Mat (AGM) technology
- Sealed Construction (Non-Spillable Battery)
- Can be mounted in any orientation except inverted
- US DOT, IMDG, ICAO and IATA certified non-spillable
- Can be fitted with brass automotive terminal
- Durability - withstands shock and vibration
- Suitable for repeated discharges.

NOMINAL DIMENSIONS

Length		Width		Height		Total Height		Weight	
mm	inch	mm	inch	mm	inch	mm	inch	kg	pound
307	12.09	169	6.65	214	8.43	237	9.33	32.2	70.99

SIZE & DETAILED ILLUSTRATION

Terminal (unit:mm)

+ Positive **- Negative**

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modifications without notice. Contact Fullriver for the latest information.